

- Word Count: 3051

Plagiarism Percentage

1%

sources:

1

1% match (publications)

[Mintorogo, Danny Santoso, Wanda K Widigdo, and Anik Juniwati. "Application of Coconut Fibres as Outer Eco-insulation to Control Solar Heat Radiation on Horizontal Concrete Slab Rooftop". *Procedia Engineering*, 2015.](#)

2

< 1% match (Internet from 27-Mar-2012)

<http://www.academicjournals.org/ijps/pdf/pdf2011/4Jan/Liang%20and%20Huang.pdf>

3

< 1% match (publications)

[El Bachawati, Makram, Rima Manneh, Rafik Belarbi, Thomas Dandres, Carla Nassab, and Henri El Zakhem. "Cradle-to-gate Life Cycle Assessment of traditional gravel ballasted, white reflective, and vegetative roofs: A Lebanese case study", *Journal of Cleaner Production*, 2016.](#)

paper text:

Copyright © 2016 American Scientific Publishers Advanced Science Letters All rights reserved Vol. Printed in the United States of America Remarkable 3-in-1 Pakis-Stem Green Roofs for Saving Thermal Flat

Rooftop Danny Santoso Mintorogo¹, **Wanda K.** Widigdo¹, **Anik** Juniwati¹

1

¹Department of Architecture, Petra Christian University, Jalan Siwalankerto 121-131, Surabaya 60235, East-Java, Indonesia

The green councils in the world are often promoting green buildings in terms of energy savings by mitigating the thermal load on buildings, especially thermal rooftop, into the room. Green roofs can be the most effective to lower roof thermal in tropical regions, but complicated and costly to build a perfect green roof even for a simple extensive green rooftop. This research looks for a remarkable growing medium for constructing green roof. Pakis-stem blocks can perform a 3-in-1 function: as a light-weight growing medium for green rooftops, an easy-to-form urban farming in private buildings or residences, and an eco-friendly external roof insulation. After a deep measurement on the rooftop surface and room thermal behaviour, the pakis-stem green rooftop can reduce 16.4°C of surface dry-bulk temperature and approximately 7°C ambient room dry-bulk temperature lower compared to conventional rooftops at noon. Furthermore, the surface temperature and ambient room air temperature difference between Pakis vegetative green rooftops and miana scrub green rooftop is approximately 7°C and 3°C respectively. Keywords: The Lightest Green Roof Growing Medium, Urban Farming, Eco-friendly External Rooftop Insulation. 1. INTRODUCTION The solar radiation in Surabaya, Indonesia, is very high The urban city is growing rapidly, constructing lots of due to the sun latitude on 7°17'-21' Southern hemisphere new landed houses, middle high-rise offices, and

tall and longitudinal 112o 47' East. Table 1 indicates the commercial buildings, resulting in more hard surfaces monthly average horizontal global solar radiation, that has (pedestrians' sidewalk, parking lots, concrete rooftops) around 400 Wm-2 in dry seasons and 300 Wm-2 in rainy than green open spaces (gardens, urban forests, children seasons in the year of 20083. playground yards, and city parks) which leads to Urban Heat Islands (UHI).Urban Heat Islands in a city tends to be Table.1. Surabaya's Monthly Average Horizontal warmer (around 1-3oC) at a calm nighttime than the Global Solar Radiation (Wm-2) in 2008 surrounding sub-urban and rural areas¹. On a sunny day, Dry seasons Rainny seasons rooftop and pavement surfaces exposed to solar radiation tend to have surface temperature 27o to 50oC¹ hotter than May 369 January 327 the ambient air temperature (around min. 22.6o to max. June 360 February 255 33.7oC) in the city of Surabaya, Indonesia². One way to mitigate UHI is planting larger and lushier July 382 March 297 trees and using reflective surfaces (cool roofs), as well as August 414 April 357 planning green roofs or vegetable roofs and porous September 415 November 304 pavements. The intensity of solar radiation, which mostly causes the heat in any countries, is deposited in those October 440 December 271 materials. Average 397 Average 302 *Email Address: dannysm@petra.ac.id The research objectives are: First, looking for an easy-to-remove or attachable growing medium for the type of extensive green roofs; Second, finding the new light- weight growing medium that will fit on the existing rooftop structures; Third, promoting extensive-green-rooftop urban farming, which will create a better outdoor ambient thermal environment and mitigate the UHI effect⁴. High solar radiation intensity impacts on concrete rooftop, especially on the flat bare roofs which are not covered by any external insulations, let alone unused outdoor rooftop spaces. It becomes a huge source of thermal roof, affecting the cooling load and the UHI. To solve this problem, a new organic material called Pakis-stem, which comes from Pakis trees (figure 1 left), is cut into blocks (figure 1 right), which then are used to create remarkable 3-in-1 result. First, it becomes the lightest and easiest growing medium for extensive green roofs; Second, it promotes urban farming (resulting in sustainable economic: People can plant organic vegetables on their rooftops, even on commercial buildings'); third, it acts as as external eco-friendly insulation to mitigate the flat rooftop thermal. The eco-friendly material: Pakis-stem (the lightest growing medium of green roofs) Fig.1. A Pakis tree (left), the cut Pakis-stem blocks (right) Table 2. Pakis Dimensions and Weights consists of roughly 33 blocks, and dry Pakis blocks weigh almost 5 kilograms per square meter, whilst wet pakis blocks (immerse in water) weigh nearly 7.3 kilograms. There is a 10-gram difference in weight between the large pakis size and the small one, both in dry and wet condition⁵. To build a conventional green roof, either extensive or intensive,one will need to construct complicated component layers. All those components cause extra weights to the roof structure, either for new or old buildings⁶, creating expensive building cost. That is why not every flat rooftop building assembles green roofs (figure 2). Fig.2. A Conventional Extensive Green Roof Compared to the conventional extensive green rooftops, special encouraging Pakis-stem block rooftops are less complicated to build on the top of existing roof structures. Pakis-stem green rooftop layers can be installed on old and new structure buildings without altering too much construction (figure 3). Fig. 3. Pakis-Stem Blocks Extensive Green Roof Urban farming (agricultural green rooftop) Plants used for the extensive green roofs are mostly grass, flowers, sedum, sempervivum and saxifraga, all of those which belong to succulent species. Succulent plants are not suitable for longer rainy seasons, as it will hold too much water on the growing medium. If green roofs are considered to contribute to a sustainable urban environment/city, agricultural or crop growing green roofs can be considered more to construct⁷. In Hong Kong, several pilot studies on sustainable rooftop farming had been done, for example, vegetables, herbs, (Source: Sam C.M. Hui) Fig. 4. Urban farming for green roofs in a primary school The research does not use conventional soil for growing medium. Instead, it uses pakis stem blocks as organic material to achieve easy, neat, and eco-friendly growing substance. Pakis-stems come in two different sizes and types; porous and semi-solid (denser stalks). The dimensions, weights and sum of blocks in one square meter Pakis stem sold in the

flower market have two different sizes, as shown in table 2. One square meter of small Pakis stem in Hong Kong (pilot study) 2 watermelon, and green beans have been planted successfully on a primary school (figure 4). 2. LITERATURE REVIEW Many professionals have constructed typical intensive or extensive green roofs by means of soil as a growing medium. The purpose of constructing a green roof is mostly to measure the reduction of the rooftop surface and the ambient air temperature, as well as

the surrounding reflected long-wave radiation due to the rooftop

2

lawn8. Wong N.H, in his research on comparing intensive and extensive system of green roofs, showed that the surface temperature of the intensive green roof (without any green plants) on bare soil could reach 57oC. Meanwhile, the surface temperature of the extensive system can reach approximately 60oC, and over 70oC on the metal roof system9. Another research had been done on extensive green roof with three different plants, which are Sedum Spurium (LS), Sedum Kamtchaticum (PK), and Sexangulare (LA). The result was that a combination of lava rocks and Sedum Spurium (LS) is the best roof insulation in reducing the rooftop thermal10. A field-measurement research study on thermal evaluation of green roof presented in

the first North American Green Roof Infrastructure Conference in Chicago

3

pointed out that green roof layers could mitigate the rooftop surface temperature fluctuations to around 45oC lower compared to the reference rooftop (conventional flat bare rooftop). In addition, the green roof membrane can reduce the temperature fluctuation to approximately 6oC a year11. 3. RESEARCH METHODOLOGY Measurement instrument Two sets of measurement instrument from ONSET – American company were used for measuring ambient air temperatures and flat rooftop surface temperatures. HOBO data logger U12 can measure ambient air temperature (-20o to 70oC) (fig. 5A) and external TMCx-HD water/soil temperature sensor probe can measure surface temperature (air/surface: -40o to 100oC) (water: -40o to 50oC) (fig. 5B). Fig. 5. HOBO data logger U12 (A), thermal probe (B) Vegetable plants Two types of vegetables were observed to find out the 3 most suitable and sustainable shading domain (the level of density of the leaves). The vegetables were green selada keriting (lettuce) (fig. 6 A) and sawi hijau (mustard greens) (fig. 6 B). (A) (B) Fig. 6. Baby selada keriting hijau (A), sawi hijau (B) Tested Models Two types of built-model were used. One model represented the conventional flat concrete rooftop, and the other represented a green roof covered with pakis stem blocks as a growing medium on which those vegetable seeds are planted (measuring for a week) (fig. 7). Then, the detachable polybags of miana plants were substituted with pakis-stem blocks, and were measured for another week. (fig. 8). Fig. 7. The two tested models: (A) represented the conventional flat roof model, (B) represented the green model for measuring with Pakis-stem blocks slada keriting and miana plants (C). Fig. 8. The tested Green roof model with removable miana scrubs in polybags. Pre-tested for thermal balancing of the test models Two types of built-model were pre-tested to find the thermal balance on both models. Pre-measuring of the two models took place for two weeks. The thermal results both the surface temperatures and the room model ambient air temperatures were almost equal (Tabel 3). Tabel 3. Pre-tested surface and room model temperatures Research procedures The two test models were tested for two months, starting from June to July. In each month, the thermal data was separated into two categories: on hot days (full-day sun for gathering maximum rooftop and room model ambient dry-bulk temperature behavior). Furthermore, the data of surface and

room model temperatures in one month was calculated to find the average. The Pakis-stem model was built in these steps. First, the Pakis-stem blocks were laid down on a flat concrete rooftop of the tested area, which was on the rooftop (7th floor) of Petra Christian university. Two kinds of seeds (selada keriting and sawi hijau) were planted on the pakis stem blocks, then were sprayed lightly with water by using water sprinklers (to make sure the seeds did not fall down into the Pakis-stem blocks). After around 3 weeks, selada keriting and sawi hijau, along with the Pakis blocks were moved to the green rooftop model to start the thermal measurement (fig. 9). After a week measuring on pakis- stem blocks with selada keriting, the miana scrub was also measured for a week on green rooftop model. Fig. 9. Seeding on the top of pakis blocks (A), Spraying water gently (B), Sprouts appearing after 3 weeks (C).

4. EXPERIMENT RESULTS

Vegetated Rooftop

After planting and moving those two types of vegetables to the Pakis-stem green roof model in the third week, only selada keriting hijau had a prolific growth (fig. 10 A & B, selada keriting is planted on the green model). A month after, sawi hijau still did not grow well compared to selada keriting hijau. Sawi hijau may have to be planted another time (fig. 10 A, behind selada keriting). Both vegetables on Pakis green rooftop model were sprayed plain water twice a day except in rainy days. After 1.5 months, the vegetables were watered only once a day or every two days due to the thickness of the Pakis growing medium (3 layers are around 9-10 cm). Fig. 10. Vegetables on green roof model (A), Selada keriting after two months (B), Thermal characteristics on tested models

The data of surface temperatures and ambient air temperatures, as well as the average, of the room reference model and pakis green model were categorized under hot, cloudy and rainy condition. The data includes the tested results on both models (reference model and Pakis green model) in June and July 2016, Table 4.1 shows the measurements average data on both ordinary flat roof model (Reference Model) and Pakis green roof model with planted vegetables green selada keriting in June and July 2016. Flat roof surface temperature and room model temperature had the same values in June and July. There was 0.5oC temperature differences between surface and ambient room temperature on the green model in June, and 0.7oC temperature differences in July (table 4). Tabel 4. Average surface and ambient air room temperatures on reference and Pakis green models (June & July 2016)

Figure 11 shows the comparison of the surface temperatures on common flat bare rooftop, Pakis-stem blocks green rooftop, and Miana flower plant green rooftop. Not being covered with a growing medium and plant involvement on hard rooftop surface, the maximum temperature of the hard surface can get to around 45oC at noon, to two hours after noon. The daytime (6 am – 6 pm) daily variation of maximum surface temperatures was around 21oC, and the night time (6 pm – 6 am) daily surface temperature variation was around 4oC. With the installed vegetation, the maximum surface temperature of Pakis- stem blocks and lettuce was around 30oC. Meanwhile, with installed Miana scrubs, the maximum surface temperature was about 35oC. Selada keriting green roof had the lowest thermal performances compared to the Miana scrub green rooftop and conventional roof on daytime. The dry-bulk surface temperature difference of the Pakis-stem green roof to Miana scrub rooftop, and to the conventional rooftop were 12oC and 16.4oC respectively. Nevertheless, the nighttime (6 pm to 6 am) surface thermal performances of the Pakis green rooftop were around 2oC higher compared to the thermal surface reference model, and 3oC higher compared to the Miana scrub green rooftop at 6 am (fig. 11).

4 Fig. 11. Average surface temperatures on reference, pakis- stem and miana scrub green rooftop on hot days in June 2016

The thermal surface of Pakis green rooftop could lower the temperatures due to the Pakis-stem blocks and vegetables on the top of it, which acted as an external roof insulation (protecting rooftop from the heat of solar radiation) during daytime. On the contrary, the stored heat on the rooftop trapped in Pakis green roof and Miana scrub polybag green roof was hard to lose heat, or slow to release to the cool night sky because something blocked the surface of the green rooftop. That is why the thermal surface performances on conventional rooftop were better during the nighttime. The conventional flat rooftop was free to lose the stored heat once the outdoor ambient air temperature was lower than the stored heat. Fig.

12. Average room model temperatures on reference, pakis and miana scrub green rooftop on hot days in June 2016 After having surface temperatures measured from all systems (conventional, Pakis, and Miana scrub green roofs), the room ambient air temperatures of both models can be calculated. The ambient air temperature on the conventional rooftop model was the highest compared to the Pakis-stem selada keriting and Miana scrub rooftop. The Pakis-stem blocks selada keriting green roof had the lowest ambient air temperatures during daytime. It can be noticed from figure 12 that the room thermal of Pakis-stem vegetative green roof was about 7°C lower than the conventional flat bare rooftop, but it was still 3°C lower compared to the same green rooftop (Miana scrub) during the daytime.

4. CONCLUSIONS Along with the conventional roof as the reference model, two different combinations of growing medium and vegetation in a built-up green roof models were tested simultaneously. The varying parameters of the tests were the growing media; Pakis-stem blocks and soil in polybags. Two vegetation types were planted; selada keriting as urban farming vegetation and Miana scrub as green roof flower. Selada keriting on Pakis-stem blocks vegetative green rooftop turned out to have the lowest thermal performances compared to the Miana scrub green rooftop and the conventional rooftop. The daily temperature differences between the two rooftops (the conventional and Miana scrub rooftop) and the inside ambient air temperature were the lowest. The thermal surface fluctuation differences of the Pakis-stem selada keriting green roof to the Miana scrub green roof and to the conventional flat roof at noon time were 7°C and 16.4°C. The Ambient room air temperature differences were 3°C to miana scrub rooftop and 7°C to common flat rooftop at noon. Those room thermal differences are huge for energy saving. Pakis-stem blocks, as a growing medium, as a sustainable urban farming domain, and as an external eco-friendly insulation for a green rooftop, demonstrate to be very effective, easy to construct, and is low maintenance.

REFERENCES [1] E. Wong, K. Hogan, J. Rosenburg, A. Denny. Reducing urban heat islands: compendium of strategies, Urban heat islands basics. The Climate Protection Partnership Division in the U.S. (2000). [2] The Central Bureau of Meteorological Station at Juanda Surabaya: Average maximum and minimum air temperature, (2013) [3] D.S. Mintorogo, Surabaya's horizontal and tilted global solar irradiation in 2009, Research report, Petra Christian University (2010). [4] N.H. Wong, Y. Chen, C.L. Ong, A. Sia. Investigating of thermal benefits of rooftop garden in the tropical environment. *Journal of Built Environment*, 38(2)(2003) 261-270. [5] D.S. Mintorogo, Application of pakis-stem as insulation to control heat gain on concrete flat roof, Thesis doctor of philosophy (architecture). Universiti Teknologi Malaysia (2014). [6] E.J. Grant, A decision-making framework for vegetated roofing system selection, Thesis doctor of philosophy (architecture and design research). Faculty of the Virginia Polytechnic Institute and State University (2007). [7] Sam C.M. Hui. Technical guidelines for green roofs systems in Hong Kong, CIBSE Hong Kong Branch. (2011) 39. [8] Liang H.H. & Huang K.T. Study on rooftop outdoor thermal environment and slab insulation performance of grass planted roof, *Journal of Physical Sciences* 6(1)(2011) 65-73. [9] Ntro.Hpi.cWalocnlgim,Ya.teC,hPerno.cAeecdoinngpaorfis2onnd olfnttweronartoioofntaolpCsoysntfeemresnicne tohen Harmony in Culture and Nature, Yogyakarta, (2006) B14 1-8. [10] Celik S., Morgan S., Retzlaff W.A. Energy conservation analysis of various green roof systems. A research report, (2008). [11] Liu K., Baskaran B. Thermal performance of green roofs through field evaluation. *Proceeding for North American green roof infrastructure conference, award and trade show, IL. Chicago* (2003) 1-10. Received: August 19, 2016. Accepted: August 23, 2016

The Remarkable 3 in 1 Pakis-Stem Green Roofs for Saving Thermal Flat Rooftop The Remarkable 3 in 1 Pakis-Stem Green Roofs for Saving Thermal Flat Rooftop The Remarkable 3 in 1 Pakis-Stem Green Roofs for Saving Thermal Flat Rooftop 1 5