

 \Box *NOTICE*: Ensuring subscriber access to content on IOPscience throughout the coronavirus outbreak - see our remote access guidelines.

Table of contents

Volume 520

2020

Previous issue

International Conference on Renewable Energy and Sustainable Built Environment 2019 14 September 2019, Bandung, Indonesia

Accepted papers received: 01 June 2020 Published online: 19 June 2020

Open all abstracts

Preface

OPEN ACCESS	011001
Preface	
← Open abstract	
OPEN ACCESS	011002
Peer review statement	
Paper	
OPEN ACCESS	012001
Design Of Automatic Switching System And Data Acquisition On Mobile Hybrid Solar Tracking System For Stand Alone Small PV With Reflector	
I Abadi, E H Setyawan and M Ardiansyah	
+ Open abstract 🔄 View article 🏴 PDF	
OPEN ACCESS The Effect of Fuel Filter Pore Size on B20 Fuel Filter Clogging at Low-Temperature	012002
Condition	
I Paryanto, E Rismana, AD Arbianto, T Prakoso and M Gozan	
← Open abstract	

OPEN ACCESS			012003
Effect of Binder A Pellets	Adding to The Phys	ical Properties of Municipal Solid Waste (MSW)	
D Nursani, S R H Si	regar and A Surjosaty	o	
+ Open abstract	View article	🔁 PDF	
OPEN ACCESS			012004
The study of susta supplier	ainable procuremen	t in the procurement of ready mixed concrete	
T Setiadi and M Ab	duh		
	Tiew article	🔁 PDF	
OPEN ACCESS Production of Bic Fermentation Met	ethanol from Napie thods	er grass: Comparison in Pre-treatment and	012005
Taufikurahman, She	rly, Jessica and W O I	Delimanto	
	View article	PDF	
OPEN ACCESS Factors Influencin C Meidiana, A Hida	ng the Biogas Accej yah and W P Wijayan	ptance in Rural Area	012006
	View article	🔁 PDF	
OPEN ACCESS Preliminary Desig Anaerobically Dig	gn of Phycocyanin I gested Dairy Manu	Production from <i>Spirulina platensis</i> Using re Wastewater	012007
T Taufikurahman, D	P A Ilhamsyah, S Ro	santi and M A Ardiansyah	
	View article	🔁 PDF	
OPEN ACCESS Biorefinery Appro	oach for Biodiesel I	Production from Microalgae	012008
+ Open abstract	View article	🔁 PDF	
OPEN ACCESS Heat Transfer Cha Cooling Process t M Irsyad, M Akmal	aracteristics of Para o Room Cooling A , M D Susila, Amrizal	ffin in Staggered Fins Heat Exchanger for the pplications and Amrul	012009
OPEN ACCESS			012010
			012010

A Prototype of Monitoring Temperature and Humidity on Photovoltaic Using ESP8266

OPEN ACCESS The Effect of Ligl			
OPEN ACCESS The Effect of Ligl			
The Effect of Light			(
	hting, Aeration and	l Stirring on Industrial Synthetic Resin Wastewater	
Model Treatment	by Using Tubular	Bioreactor	
M Y A Ramadhan, A	A F P Harahap, H Ha	rtono and M Gozan	
+ Open abstract	Tiew article	🔁 PDF	
OPEN ACCESS			(
Cooling Load Ana Simulation	alysis in Asrama K	inanti 1 UGM Using Building Performance	
S A Baskara, G S A	di, S S Utami, B Pray	itno and FX P J Guntoro	
✤ Open abstract	View article	🔁 PDF	
OPEN ACCESS			(
Developing Refer	ence Building for	Campus Type Buildings in Universitas Gadjah Mada	
S S Utami, A Sihota	ng, B Ardiyanto and	B Prayitno	
	View article	PDF	
1			
OPEN ACCESS			
Implementation o	f 10% Cutting Mov	vement in Building a Lighting System on	
Postgraduate Dipo	onegoro University	7	
R W Wijayanti, E Pı	rianto and J Windarta		
	View article	🔁 PDF	
1			
OPEN ACCESS			
The Study of the S	Smart City Concep	t Development, Based on Public Open Space	
Elements (case str	udy: Kambang Iwa	ık and Opi Jakabaring Lake)	
F Amalia, M Hanum	n, R Drastiani and M	L Tondi	
	View article	🔁 PDF	
OPEN ACCESS			(
Effect of Tilt Ang Wind Pressure an	le of Building-Inte d Solar Radiation	grated Wind Turbine and Photovoltaic Façade on	
D S Mintorogo, F El	lsiana and A Budhiya	nto	
	View article	🔁 PDF	

2020	IOP Conference S	eries: Earth and Environmental Science. Volume 520, 2020 - IOPscience
B G Dewanto, D N	ovitasari, Y C Tan, D I) Puruhito, Z A Fikriyadi and F Aliyah
	View article	PDF
OPEN ACCESS Identification of	Ideal Thermal Settin	gs for Administration Office on Hot-Humid Climate
N D Salsabila, N H	. Ibrahim, T N T Syahi	rani, Y T Tanzil and O C Dewi
	Tiew article	🄁 PDF
OPEN ACCESS Sustainable Hybr	id Village: Regenera	ation of Settlement in Jatinegara, Indonesia
T Endangsih, B PraOpen abstract	yitno and A Kusumaw	PDF
OPEN ACCESSExperts OpinionSahid, Y Sumiyati a+ Open abstract	on Building Passive and R Purisari TView article	Strategy Performance
OPEN ACCESS Planning and Des Universitas Pend	signing UPI Science idikan Indonesia	and Techno Park as a Green Campus Center in
F F Devitama, B Pa	ramita and N A Ardiar	ni
	View article	PDF
OPEN ACCESS Efficiency Energ	y on Office Building	g in South Jakarta
M Amana, B Paran	ma, K Minggra and M	D Koermawan

🔁 PDF View article + Open abstract

OPEN ACCESS	012023
Pedestrian-Friendly for Redesign Leuwipanjang Integrated Terminal with Wayfinding Approach	
A N Hanissa, B Paramita, T Megayanti and M D Koerniawan	
← Open abstract	
OPEN ACCESS	012024
Transit Integrated Design in Poris-Plawad Tangerang Transit Oriented Development Area: Terminal and Station	
A S Nabila, B Paramita, R Minggra and M D Koerniawan	

View article 🔁 PDF + Open abstract

012018

012019

012020

012021

012022

OPEN ACCESS			012025	
The prototypes of energy-efficient residential Building with metal roof in Gorontalo, Indonesia				
M Jahja, A Gunawa	n, A N F Syamsul, Y	I Arifin and M D Koerniawan		
+ Open abstract	View article	🔁 PDF		
OPEN ACCESS			012026	
Sustainability Pot Nantu Boliyohuto	tential for Renewab Wildlife Reserve	ble Energy System in Isolated Area that Supports		
F Pontoiyo, M Sula	iman, R Budiarto and	D Novitasari		
	View article	🔁 PDF		
OPEN ACCESS Sustainability De	sign on Use of Bio	mass Waste Gasification Technology for Small	012027	
Industry of Palm	Sugar in Sinarlaut	Village		
R Budiarto, I Arnif,	A R Wardhana, D No	ovitasari and B Margono		
	Tiew article	🔁 PDF		
JOURNAL LINK	S			
Journal home				
Information for orga	anizers			
Information for auth	iors			
Search for published	d proceedings			
Contact us				

Reprint services from Curran Associates

PAPER • OPEN ACCESS

Effect of Tilt Angle of Building-Integrated Wind Turbine and Photovoltaic Façade on Wind Pressure and Solar Radiation

To cite this article: D S Mintorogo et al 2020 IOP Conf. Ser.: Earth Environ. Sci. 520 012016

View the article online for updates and enhancements.

Aris Budhiyanto

as PRESENTER

of the paper entitled "The Effect of Wind Pressure and Solar Radiation on Regular and Tilted Façade for Building Integrated Wind Turbine and Photoltaic."

RE

September 14th, 2019 Luxton Hotel, Bandung, INDONESIA

Dr.Eng. M. Donny Koerniawan

Coordinator International Conference on Renewable Energy and Sustainable Built Environment Dr. Rachmawan Budiarto, ST., MT.

Director Center for Development of Sustainable Region (CDSR)













SURAT PERNYATAAN KLARIFIKASI

Surabaya, 13 Februari 2024

Perihal: Penjelasan Terkait Perbedaan Judul pada Sertifikat Konferensi dan Publikasi Prosiding

Dengan hormat,

Bersama surat ini saya menyatakan bahwa publikasi dengan judul 'Effect of Tilt Angle of Building-Integrated Wind Turbine and Photovoltaic Facade on Wind Pressure and Solar Radiation' merupakan publikasi prosiding yang dipresentasikan dalam konferensi International Conference on Renewable Energy and Sustainable Built Environment 2019, tgl. 14 September 2019, Bandung, Indonesia.

Terkait judul 'The Effect of Wind Pressure and Solar Radiation on Regular and Tilted Façade for Building Integrated Wind Turbine and Photoltaic' yang tertera di sertifikat konferensi, kami menjelaskan bahwa judul tersebut adalah judul dari abstrak yang kami kirimkan. Abstrak dan acceptance letter dari panitia konferensi terlampir bersama surat ini.

Perbedaan judul antara publikasi prosiding dan judul yang tertera di sertifikat konferensi dikarenakan adanya saran dan diskusi saat artikel tersebut dipresentasikan, yang berdampak adanya revisi pada artikel tersebut dan mempengaruhi judul artikel publikasi prosiding.

Demikian surat pernyataan ini dibuat.

Hormat saya,

Aris Budhiyanto

The Effect of Wind Pressure and Solar Radiation on Regular and Tilted Façade for Building Integrated Wind Turbine and Photoltaic

Danny S. Mintorogo, Feny Elsiana, Aris Budhiyanto

Architecture Department, Petra Christian University

Abstract

This study investigated the potential impacts of wind pressure and incident solar radiation on building tilted façade installed with micro wind turbine and photovoltaic as second skin facade for generating electricity. The wind pressure will affect wind turbine rotations and solar radiation will affect energy produced by the photovoltaic. The study used simulation modelling software to analyze the wind pressure and solar radiation received on the tilted façade. The research found that the smaller tilted angel of the façade the larger wind pressure received by the wind turbine and the more solar radiation received by the photovoltaic. Conversely, the larger tilted angle of the building façade, the less radiation received by the photovoltaic, despite the wind pressure received by the wind turbine is higher than the wind pressure received by 90⁰ tilted angle façade (regular façade). However, the more radiation received by the façade, the more heat received by the building.

Keywords: wind pressure, solar radiation, simulation, building facade



Bandung, 06/Sep/2019

Acceptance Letter

To Whom It May Concern

Congratulations!

Now we are pleased to inform you, **Aris Budhiyanto**, that your extended abstract has been accepted for publication and you are cordially invited to to present your paper on the **International Conference on Renewable Energy and Sustainable Built Environment** on **14th September 2019 at Luxton Hotel, Bandung, Indonesia**.

ICRESBE 2019 is a conference that focuses on renewable energy technology, especially in biofuel and microalgae, as well as the development of Net Zero Energy Building (NZEB) as one of the solutions for sustainable built environment. ICRESBE is an initiative from Center for Development of Sustainable Region (CDSR) through the Sustainable Higher Education Research Alliance (SHERA) Program, funded by USAID. This conference provides opportunities for delegates to exchange new ideas and experiences to establish research relations and future collaboration.

If you have any questions, please do not hesitate to contact us via<u>icresbe2019@gmail.com</u>. For more updated information, please visit conference website: <u>http://www.icresbe.com/</u>

Following are the details of your accepted submission:

Aris Budhiyanto is author/co-author of the following accepted contribution(s):

The Effect of Wind Pressure and Solar Radiation on Regular and Tilted Façade for Building Integrated Wind Turbine and Photoltaic Author(s): Mintorogo, Danny S.; Elsiana, Feny; Budhiyanto, Aris Presenting Author: Budhiyanto, Aris Submission Type / Conference Track: Extended Abstract Submission Status: Accepted

We are looking forward to meeting you.

Thanks for your support!

Yours sincerely,



Nissa Aulia Ardiani Secretary ICRESBE19 International Conference ORGANIZING COMMITTEE Center of New and Renewable Energy Development Institut Teknologi Bandung Jalan Ganeca 10, Bandung 40312, INDONESIA E-mail: <u>icresbe2019@gmail.com</u>

IOP Publishing

Effect of Tilt Angle of Building-Integrated Wind Turbine and **Photovoltaic Facade on Wind Pressure and Solar Radiation**

D S Mintorogo, F Elsiana and A Budhiyanto

Architecture Department, Petra Christian University E-mail: arisb@petra.ac.id

Abstract. This study investigated the potential impacts of wind pressure and incident solar radiation on a building tilted facade installed with micro wind turbine and photovoltaic panels as a second skin façade for generating electricity. The wind pressure will affect wind turbine rotation, and solar radiation will affect the energy produced by the photovoltaic. The study used simulation modeling software to analyze the wind pressure and solar radiation received on the tilted facade. The research found that the force received by the tilted facade is more significant than that received by the 90° tilted façade. The smaller the tilted-angle of the façade, the more radiation received by the PV panel. Conversely, the larger tilted-angle of the building facade, the less radiation received by the photovoltaic, despite the wind pressure received by the wind turbine being higher than that received by the 90° tilt facade. However, the more radiation received by the façade, the more heat received by the building.

1. Introduction

Energy conservation has become a significant concern around the world as buildings are built taller and consume more energy—about 30-40% of all primary energy is accounted for by buildings [1]. While fossil fuels are getting scarce and the price is unstable as well as the power generation from fossil fuels engenders environmental problems, the attempt to harness renewable energy, especially wind and solar energy, is much improved [2]. Building-integrated photovoltaic (BIPV) as well as building-integrated wind turbine (BIWT) systems have been developed to serve that purpose.

The Bahrain World Trade Center is the first building integrated with three sets of turbines, each of which has a diameter of 29 m. The Miami Cor Tower utilizes wind energy by installing multiple horizontal wind turbines in four exterior walls at the top of the building [3]. BIWT can be applied on high-rise buildings as one or a few large-size wind turbines, or as many small-size wind turbines on the buildings instead of a few large-size wind turbines [4]. Installing many small-size wind turbines does not require any specific structural strengthening. Still, the total output power from this system would be considerably lower than that from large-size wind turbines because their installable area is limited to such areas as rooftops and edges of buildings, and the diameter of the wind turbine is smaller. Therefore, to get enough electricity, a lot of wind turbines are needed. Installing a wind turbine on building facade should consider the shape of the buildings because it is a significant determinant of airflow patterns around buildings, and the wind flow is much dependent on the precise form of the architecture [5,6].

The shape of the building affects not only the wind flow but also the incident solar radiation on the building façade, which is the primary energy source for the BIPV system. PV panels have been developed to be installed as building elements, such as vertical claddings, windows, and shading devices. However, to increase BIPV efficiency, the PV modules' direction and inclination angle need to be

Content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence. Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI. Published under licence by IOP Publishing Ltd 1

considered [7]. For example, in Singapore, an east-facing façade and panel slope of $30-40^{\circ}$ is the most suitable location and inclination while in Indonesia, west-oriented PV panels with a 30° inclined angle generate more energy than PV panels facing other directions [8].

In this paper, an innovative building-integrated wind turbine and photovoltaic and (BIWtPv) system is proposed as a second skin façade that not only produces electricity but also reduces heat received by the building. As a Savonius-type wind turbine is installed on the building, the wind pressure and solar radiation received by the PV installed on the second skin façade should be analyzed.

2. Proposed Model



Figure 1. Wind flow pattern around a high-rise building [9]

Because the wind approaching a high-rise building is partly guided over the building, slightly around the vertical edges, and partly deviated to the ground-level (Figure 1), a Savonius-type wind turbine is used. The turbine is the simplest model and works due to the difference of forces exerted on each blade. The concave part of the wind flow catches the wind and forces the blade to rotate around its central vertical shaft. Otherwise, the convex side of the wind flow causes the blade to be deflected sideways around the shaft. Hence, concave edges with more drag force than the other half-cylinder will force the rotor to rotate [10]. In this proposed design, the Savonius wind turbine will be installed horizontally on the building façade to utilize the wind guided over the vertical façade of the building (Figure 2).



Figure 2. Savonius wind turbine (A) and wind turbine design installed on the building (B)

Instead of a large-size wind turbine, some small wind turbines and PV modules are installed on the second-skin façade. In a densely built city, high structures generate high wind turbulence and speed fluctuations, diverting the wind direction and potentially reducing its speed [11]; thus, installing small wind turbines is more effective. The proposed model is shown in Figure 3. A second-skin façade integrated with a wind turbine and photovoltaic material is installed on the building façade to harness both wind and solar energy.



Figure 3. Proposed model of BIWtPv as second skin façade

3. Method

A simulation method was used in this study for calculating wind pressure and solar radiation received by the second-skin façade. A model of a BIWtPv as a second-skin façade was set up within Flow Design and EnergyPlus simulation software. Flow Design, a CFD (Computational Fluid Dynamics) software, was used to simulate and visualize various design configurations of the fluid flow. It also can predict the airflow on cars and airplanes as well as on buildings [12]. EnergyPlus is a building energy simulation software developed by the United States Department of Energy [13] that can simulate cooling/heating loads, daylighting and photovoltaic systems with repeated accurate results that have been validated through analytical, comparative and empirical tests [14]. Flow Design software was used to analyze the wind pressure received by the façade, while EnergyPlus was used to calculate the incident solar radiation.



Figure 4. Tilted wall façade models at (A) 75°; (B) 80°; (C) 90°; (D) 100°; and (E) 105°



4. Result and discussion

Table 2.	Drag fo	orce, drag	coefficient.	pressure difference	and wind speed
1	Diag it	sive, and			

Model	Drag Force	Drag Coef.	Pressure Difference	Wind Velocity
А	1935.448	1.94	12	0-1
В	2089.775	1.97	10	0-1
С	1699.244	1.59	5	0-1
D	2213.338	2.02	16	0-1
Е	1867.150	1.73	15	0-4

Tables 1 and 2 show the wind speed and wind pressure around the model. Of all models, the wind speed around the second-skin façade is the same at about 0-1 m/s, except in Model E, where the wind speed is around 0-4 m/s. Different from the wind speed, the wind pressure around the façade is different for all models. Among all models, the pressure difference of Model C is the smallest, indicating that a 90° tilted second-skin façade is less efficient for installing a wind turbine compared with the other tilted façades. There was no significant pressure difference between Models A and B. The same occurs between Models D and E despite the pressure on Models D and E being higher than on Models A and B. This indicates that a façade tilted at less than 90° is more effective.

Savonius wind turbine performance is based on the difference between the drag force that concerns the rotor surface and the amount of drag force required to rotate the turbine shaft [15]. Among all models, the drag force and drag coefficients for Models B and D are higher than for the other models, and it indicates that the potential of wind turbine rotation is higher than for the different models. On the contrary, the drag force and drag coefficient of Model C is the lowest, indicating that the wind turbine rotates less than in the other models. However, the higher drag force could result in damage to the building façade [12].



Figure 5. Solar incident radiation on second skin façade



Figure 6. Surface heat gain on the east façade

Figure 5 shows solar radiation obtained on the second-skin façade. It is obvious that the higher the tilt angle of the wall, the smaller the solar radiation obtained. The highest solar radiation is obtained for Model A (about 313.91 W/m2), while solar radiation obtained by Model E's façade is the lowest (about 202.22 W/m2). The higher the solar radiation, the more effective the PV panel in producing electricity. However, the more solar radiation received on the façade, the more the heat gain. Figure 6 shows the surface heat gain obtained on the walls of all models. As solar incident radiation on Model A is the highest, the surface heat gain on the façade is also the highest (over 50 W/m2).

5. Conclusion

In this paper, a second-skin façade integrated with a wind turbine and photovoltaic panels is analyzed at different tilt angles. The study indicates that models with a tilted façade provide better performance for

wind turbine installation than the 90° tilt angle façade model because the pressure difference around the façade is higher as well as the drag coefficient. However, a higher drag force could destroy the wind turbine installed on the building façade. Considering that the 75° tilt angle façade model can received solar radiation higher than the other tilted façades and it produced more electricity, the façade model with a 75° tilt angle produced more energy than different models, however the heat gain received by the building was larger than for the other models.

Acknowledgements

This research was supported by the Architecture Department of Petra Christian University and funded by The Ministry of Research, Technology and Higher Education of Indonesia.

References

- [1] Lee J, Park J, Jung HJ and Park J 2017 Renewable energy potential by the application of a building integrated photovoltaic and wind turbine system in global urban areas *Energies* **10** 2158
- [2] Chong WT, Pan KC, Poh SC, Fazlizan A, Oon CS, Badarudin A and Nik-Ghazali N 2013 Performance investigation of a power augmented vertical axis wind turbine for urban highrise application *Renew. Energy* 51 388
- [3] Zhou H, Lu Y, Liu X, Chang R and Wang B 2018 Harvesting wind energy in low-rise residential buildings: Design and optimization of building forms *J. Clean. Prod.* **167** 306
- [4] Park J, Jung HJ, Lee SW and Park J 2015 A new building-integrated wind turbine system utilizing the building *Energies* **8** 11846
- [5] Bharat A and Ahmed AS Effects of High Rise Building Complex on the Wind Flow Patterns on Surrounding Urban Pockets *Int. J. Eng. Res. and Dev.* **4** 21
- [6] Kormaníková L, Achten H, Kopriva M and Kmet S 2018 Parametric wind design *Front. Archit. Res.* 7 383
- [7] Mintorogo DS 2000 Strategi aplikasi sel surya (photovoltaic cells) pada perumahan dan bangunan komersial *Dimensi Teknik Arsitektur* **28** 129
- [8] Budhiyanto A, Suryabrata J and Saragih S 2017 Study of shading device building-integrated photovoltaic performance on energy saving *J.Urban Environ. Eng.* **11** 202
- [9] Moonen P, Defraeye T, Dorer V, Blocken B and Carmeliet J 2012 Urban physics : Effect of the micro-climate on comfort, health and energy demand *Front. Archit. Res.* **1** 197
- [10] Wenehenubun F, Saputra A and Sutanto H 2015 An experimental study on the performance of savonius wind turbines related with the number of blades *Energy Procedia* **68** 297
- [11] Loganathan B, Chowdhury H, Mustary I, Rana MM and Alam F 2019 Design of a micro wind turbine and its economic feasibility study for residential power generation in built-up areas *Energy Procedia* 160 812
- [12] Amri SB and Syukur LOA 2017 Analisis aliran angin pada atap miring melalui uji simulasi flow design Langkau Betang Jurnal Arsitektur 4 136
- [13] Crawley DB, Lawrie LK, Winkelmann FC and Pedersen CO EnergyPlus: New capabilities in a whole-building energy simulation program *7th Int. IBPSA Conf.* (Rio de Janeiro) p51
- [14] Pereira W, Bogl A and Natschlager T 2014 Sensitivity analysis and validation of an EnergyPlus model of a house in Upper Austria Energy Procedia 62 472
- [15] Pamungkas SF, Wijayanto DS, Saputro H and Widiastuti I 2018 Performance 'S' type savonius wind turbine with variation of fin addition on blade *IOP Conf. Ser.: Mater. Sci. Eng.* 288 012132